






This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
4		AS DRAWN BY CANAM.	11/4/2014	JAG	
5	14-0207	CH'D CHAMFER ON Ø.890 HOLE WAS 2X .03 X 45° IS 2X .04 X 45°. CH'D DIM WAS Ø2.06 IS Ø2.05.	11/4/2014	RJC	JAG
6	15-0092	ADDED MATERIAL H1075.	4/22/2015	RJC	JAG
7	15-0271	ADDED UP ARROW NOTE. CH'D DIMS WAS 1.14 IS 1.14 +.00 -.02. WAS 2.21 IS 2X 2.21. DELETED DIMS Ø.90, Ø15/16, R.07. ADDED BREAK EDGE NOTE. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	9/22/2015	DPD	JAG
8	17-0064	UPDATED TO NEW STANDARDS. CH'D DIM WAS R.07 IS R.13, WAS 2X 10-32 UNF ∇ .25 IS 2X 10-32 UNF-2B ∇ .25. ADDED NOTE MACHINE ENGRAVE BATCH NUMBER.	3/17/2017	SM	JAG



ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS
			SWA6A-200	1	UPPER END	SS 17-4, H1150, H1075	

DART AEROSPACE			
TITLE UPPER END			REV 8
DWG NO. SWA6A-200			
MAT'L SS 17-4, H1150, H1075		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT TREAT		.XXX ± .005 FRACTIONS ± 1/8	
FINISH		.XX ± .01 ANGLES ± 5°	
SPEC		.X ± .1 SURFACES = 125/	
DRAWN BY: CANAM		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: DD 03/17/2017		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: AA 03/20/2017		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: JL 03/29/2017		USED ON MODEL	
APPROVED: JAG 04/03/2017			
SCALE 1:2	DATE 1/31/2002	SHEET 1 OF 1	